

Foam Making Equipment

The foam inductors are designed to feed foam concentrates at a set mixing rate into the hose line. Inductors are placed in the delivery line between the pump and the foam nozzle and can be used for medium- and also for heavy foam nozzles. The venture system creates a vacuum in the body of the inductor and the foam concentrate is picked up via a suction hose ND 19 with a Storz D 25 coupling. At the foam inlet Storz D 25 adapters are generally mounted. A mixing rate between 0% and 6% is possible. AWG-Foam inductors are also available with an individual foam pickup rate on request.

- Aluminium alloys (A)
- Copper alloys (C)

Inductor with integrated handle, body copper alloy



3502

Storz System Connection or thread

Style / Nominal size	In- and outlet Storz / thread	Mixture flow rate (l / min)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
Z2R	2 x C	200	365	165	175	4,600	20019395	DIN 14 384	C
Z2R	2 x 65	200	365	165	175	4,700	60219995		C
Z2R	2 x G 2 A	200	305	165	175	4,100	60227595		C
Z4R	2 x C	400	365	165	175	4,600	20019495		C
Z4R	2 x 65	400	365	165	175	4,700	60316595		C
Z4R	2 x B	400	365	165	175	4,900	60305595	DIN 14 384	C
Z4R	2 x G 2 A	400	305	165	175	4,050	60227695		C